

FROM STRENGTH TO STRENGTH

# ZINCALUME<sup>®</sup> ULTRA steel



GENERAL DESCRIPTION		STEEL BASE (GUARANTEED) LONGITUDINAL TENSILE	
ZINCALUME <sup>®</sup> ULTRA steel is a hot dipped 55% zinc/aluminum alloy-coated structural steel with a spangled surface and varieties yield strength (G550 and G300)		MECHANICAL PROPERTIES	
		GUARANTEED	
		G550	G300
		Yield Strength (Mpa)	min 300
		Tensile Strength (Mpa)	min 340
		Elongation on 50mm (% El.)	min 20
		180° transverse bend (L axis)	1 t
METAL COATING		STANDARD PRODUCTS	
Nominal Coating Mass (gr/sqm2) : 200 gram/m2 both surfaces Approximate Coating Thickness (micron) : 60 micron		BMT (mm)	
		WIDTH RANGE (mm)	
		G550	G300
		0.25	914, 1219
		0.30	914, 1219
		0.35	914, 940, 1219
		0.40	914, 940, 1219
		0.45	914, 1170, 1219
TYPICAL USES		NON-STANDARD PRODUCTS	
G550: Roll formed roofing and walling G300: Roll formed house framing, RWG, and garden sheds		CLASSIFICATION	
		BMT (mm)	
		WIDTH (mm)	
		Non-Standard Product 1	0.25 - 0.80
		Non-Standard Product 2	0.25 - 0.80
		Standard Width	
		Odd Width	
TYPICAL CHEMICAL COMPOSITION (%) OF STEEL BASE		Note: Common width (mm): 914, 940, 1170, 1219 Odd Width are all other width defined in the Commercial Availability Table	
Carbon (C)	0.030 - 0.070		
Phosphorus (P)	0.000 - 0.025		
Manganese (Mn)	0.015 - 0.300		
Sulphur (S)	0.000 - 0.025		
Silicon (Si)	0.000 - 0.030		
Aluminum (Al)	0.020 - 0.070		
SUPPLY CONDITION (Normal)		FABRICATING PERFORMANCE	
Coating Class : AZ 200		G550	
Surface Conditions : Passivated & Resin Coated		G300	
Bore Diameter : 508 mm ± 10 mm		Bending	Fair
Branding : yes		Drawing	Excellent
		Pressing	Limited
		Roll-Forming	Good
		Painting (pretreatment)	Excellent
		Welding	Good

STANDARDS: AS 1397:2001, AS 1365:1996, SNI 4096-2007 LSPR-004-IDN

For product identification and originality, please check the following brand along the edge of the coil reverse side:

"ZINCALUME(R) steel made by BlueScope Steel 21:26 05:03:08 08 SNI 4096:2007 LSPR-004-IDN"



Please ensure you have the current data sheet for this product

**PT NS BlueScope Indonesia**

SALES & MARKETING OFFICES:

JAKARTA:

BRI II Building 6th Floor Suite 902, Jl. Jend. Sudirman Kav. 42-46 JAKARTA 10210


Phone: (021) 5785-4150, Fax: (021) 5785-4151

SURABAYA:

Plaza BRI Level 5 Suite 507A, Jl. Basuki Rahmat 122 SURABAYA 60271

Phone: (031) 532-0526, 532-0259, Fax: (031) 532-0711

ZINCALUME<sup>®</sup> is a trade mark of BlueScope Limited.  
BlueScope is a trade mark of BlueScope Limited.  
© 2008 by BlueScope Limited. All rights reserved.  
No part of this brochure may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without written permission of BlueScope Limited.



A CHOICE MADE THAT YOU  
**NEVER REGRET**



DESIGN FLEXIBILITY



HI-TECH PRODUCTION



DURABILITY/ SECURITY



RECYCLING



THERMAL EFFICIENCY



WARRANTY



WHEN YOUR NAME IS ON THE LINE, MAKE SURE OURS IS ON THE STEEL