

Warranty No. : <Warranty # >

WARRANTY

NS BlueScope (Thailand) Limited (manufacturer of **Bluescope Zacs®** steel, warrants to < **Customer Name** > (supplier of profiled sheets) that the **Bluescope Zacs® Cool** steel if correctly installed and maintained on the < **Full Project Name** > project at < **Full Project Address** > :

Shall not perforate by corrosion for: 10 Years

* Terms and conditions apply. Please consult NS BlueScope (Thailand) Limited representative.

If the **Bluescope Zacs®** steel cladding (installed and maintained in accordance with the specific guidelines, terms and conditions attached) fails to perform as warranted due to a defect in the material, then at the sole discretion of NS BlueScope (Thailand) Limited ("NSBST") the cladding will either be repaired ,resupplied (but not installation),or compensation provided pro-rata in terms of actual performance versus warranted performance, and amount of time remaining in warranty No liability shall be accepted for any consequential loss or damages attributable to the failure.

This is to certify that representatives or agents of < Customer Name > have inspected the installed cladding, and ascertained (by best endeavours) that;

- The cladding is manufactured from prime quality **Bluescope Zacs® steel** (branded on reverse) ;-
- The cladding appears to have been properly installed (or any concerns are noted below) ; - and
- The environment in or around the structure does not appear to be abnormally or severely corrosive.

Comments: **No Inspection by NS BlueScope (Thailand) Limited**

Materials Used: **Area of Roof: < Roof Area > sq.m**

NOTE: This warranty is provided to, and can only be actioned by, < **Customer Name** > subject to the express terms and conditions attached. Failure, despite best endeavors, to identify problems with environment and/or installation during project inspection shall not preclude or limit the operation of the terms and conditions attached.



Warranty No. : <Warranty # >

WARRANTY

NS BlueScope (Thailand) Limited (manufacturer of **Bluescope Zacs®** steel, warrants to < **Customer Name** > (supplier of profiled sheets) that the **Bluescope Zacs® Cool** steel if correctly installed and maintained on the < **Full Project Name** > project at < **Full Project Address** > :

Attachment 1

No.	Description Coil ID	Coil ID
1		

Application Detail

Roof m.

No.	Building	Installation Date (dd/mm/yy)	Remark
1			

End-Use segment

Segment	Sub-segment

NOTE: This warranty is provided to, and can only be actioned by, < **Customer Name** > subject to the express terms and conditions attached. Failure, despite best endeavours, to identify problems with environment and/or installation during project inspection shall not preclude or limit the operation of the terms and conditions attached.



Warranty No. : <Warranty # >

TERMS AND CONDITIONS

This warranty is your guarantee that **BlueScope Zacs® prepainted steel**, if properly installed and maintained, will meet minimum expected performance levels for at least the warranted period (commencing from the date of installation).

However, certain specific problems and situations (listed below) must be addressed and rectified early in order to get the best possible performance and, if not rectified, may result in the warranty being void.

1. The warranty applies only to cladding and flashing made from prime quality BlueScope Zacs® steel. The Owner/Contractor is advised to check for the BlueScope Zacs® steel brand name printed on the reverse of the sheets prior to installation. Guttering, downpipes, brackets, doors and other accessories are excluded.
2. Cladding must be handled and installed in accordance with published BlueScope guidelines current at the time of installation, with particular attention to the issues listed below:-
 - a. Keep sheet dry at all times while stacked in bundles prior to installation. Wet sheet should be separated and dried to minimize risk of accelerated corrosion due to "wet stacking".
 - b. Do not cut sheet by circular saw or grinders as high temperature swarf will damage the coating.
 - c. During construction, remove swarf and other debris daily to minimize risk of localized corrosion.
3. Fasteners must comply with AS3566 Class 3 or Class 4, and be certified as such by the supplier of fasteners.
4. All fixings and associated components must be manufactured from compatible metals (COLORBOND®, ZINCALUME® steel, zinc, or aluminium) or be coated or plated in accordance with current published BlueScope guidelines. For long lasting consistency in appearance, should be made from the same material as the cladding.
5. The paint finish as supplied must not be scratched, abraded damaged, or coated with any foreign matter or incompatible material (including stack and flue deposits).
6. Product failures wholly or in part due to the following causes are not covered by this warranty.
 - a. Defects attributed to faulty design, method of manufacture or installation of the product.
 - b. Mechanical, chemical or other damage sustained during transport, handling, storage, erection or subsequent to erection.
 - c. Attack from chemical agents, fumes, liquids or solids other than direct rainfall.
 - d. Unwashed areas sheltered from normal rainfall and not regularly cleaned.
 - e. Extended contact with soil, dust, ashes, fertilizers, or moisture retaining substances.
 - f. Areas in metallic contact with incompatible materials (eg. lead, copper, carbon/graphite, or stainless steel) or subject to water run-off from such incompatible materials.
 - g. Failure to remove debris and/or failure to provide free drainage of water including internal condensation all surfaces of the product.
 - h. Failure to replace corroded fasteners.
 - i. Deterioration of the panels caused by contact with wet, green or treated timber and wet cement.
 - j. Severe marine, industrial or corrosive environments unless specifically agreed and noted.
 - k. Acts of God and falling objects, external force, explosions, fire, riots, civil commotions, acts of war, radiation, harmful gases or fumes, chemicals or foreign substances in the air or atmosphere, acts of terrorism, global warming, flooding and political disturbances including but not limited to uprising and protests.
7. Failure of the product from corrosion is defined as when the sheet is perforated. Surface rust, or minor corrosion at tension bends or cuts edges due to natural weathering does not constitute failure of the product.
8. Any defects must be informed to NSBST in writing within 30 days of the date NSBST in its sole discretion believes such defect should reasonably have been found given each individual circumstance.

NOTE: This warranty is provided to, and can only be actioned by, < Customer Name > subject to the express terms and conditions attached. Failure, despite best endeavours, to identify problems with environment and/or installation during project inspection shall not preclude or limit the operation of the terms and conditions attached.